



**SPECIFICATION**

Furnish and install Corrugated Stainless Steel Water Heater Connectors as manufactured by LSP

**DESIGN FEATURES**

- Full Flow— 3/4" ID provide greater water flow with minimal restrictions.
- High quality EPDM gasket
- Lead Free, Non-toxic and sanitary
- Truly kink free
- Flexible but durable even with multiple bends
- Tube resists work hardening allowing for more flexibility and easier installation
- Integrated dielectric sleeve, so no dielectric union required
- Defect-free tubing (100% leak tested)
- High corrosion-resistant stainless steel

**INSTRUCTIONS**

1. For use with water in accessible locations only.
2. Install inlet according to manufacturer's instructions. For outlet nut, hand tighten nut plus 1/4" turn with wrench.
3. Turn water on and check for leaks. DO NOT OVER TIGHTEN or expose to harsh chemicals.
4. Inspect every six months. Do not Re-use

**OPERATING SPECIFICATIONS**

- Temperature: 40-160°F with intermittent temps up to 180°F
- Max working pressure 125 PSI, intermittent impulse up to 180psi

**MATERIAL SPECIFICATIONS**

- Tubing: Stainless Steel
- End Connections: Brass
- Washer: High quality EPDM



3689 Arrowhead Drive, Carson City, NV 89706  
 Phone (800) 854-3215 Fax (800) 243-1777

E-mail sales@lspproducts.com Website www.lspproducts.com  
 Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.


**CORRUGATED STAINLESS STEEL WATER HEATER CONNECTORS**  
**Specification Sheet**

Part Number	Description	Length
WCS-112-PP*	3/4" FIP x 3/4" FIP	12"
WCS-118-PP*		18"
WCS-124-PP*		24"
WCS-312-PP	1" FIP x 1" FIP	12"
WCS-318-PP		18"
WCS-324-PP		24"
WCS-418-PP	3/4" FIP x 3/4" SWEAT	18"
WCS-424-PP		24"
WCS-518-PP	3/4" UPONOR PEX x 3/4" FIP	18"
WCS-524-PP		24"
WCSV-518-PP	3/4" UPONOR PEX 1/4 TURN BALL x 3/4" FIP	18"
WCSV-524-PP		24"
WCS-718-PP	3/4" PUSH TO CONN X 3/4" FIP NUT	18"
WCS-724-PP		24"
WCSV-718-PP	3/4" PUSH TO CONN. 1/4 TURN BALL x 3/4" FIP NUT	18"
WCSV-724-PP		24"
WCS-818-PP	3/4" CRIMP PEX x 3/4" FIP NUT	18"
WCS-824-PP		24"
WCSV-818-PP	3/4" CRIMP PEX 1/4 TURN BALL x 3/4" FIP NUT	18"
WCSV-824-PP		24"
WCS-918-PP	3/4" REHAU PEX X 3/4" FIP NUT	18"
WCS-924-PP		24"
WCSV-918-PP	3/4" REHAU PEX 1/4 TURN BALL x 3/4" FIP NUT	18"
WCSV-924-PP		24"
WSS-112-PP	3/4" FIP x 3/4" FIP Includes 3/4" SWEAT ADAPTOR	12"
WSS-118-PP		18"
WSS-124-PP		24"

\* Designates Not full flow

**COMPLIANCES/LISTINGS**

- IAPMO listed to the Lead Free Plumbing Law File 6545,
- IAPMO Listed to NSF/ANSI 61 File N-6614
- IAPMO listed to ASME A112.18.6/CSA B125.6 File 2111



Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	