

Extreme Angle Master Flash®

Specifically designed for **Metal Roofing Industry**



for applications with a 35 to 65 degree angle, while accepting & responding to the most commonly encountered pipe penetrations.

ISO Quality, Price & Availability / TWO COMPOUNDS

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to	Intermittent Continuous	+135°C (+275°F) +100°C (+212°F)
		+260°C (+500°F) +225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	-55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%



*Complete specification data and testing methods are available upon request.



Weather Protection Made of E.P.D.M. or Silicone,

These flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.



Adaptable Base

The base is designed to mold to most panel configurations and roof pitches regardless of pipe location.



Modification Made Simple

Easy to see pipe diameters make for painless on-site installation.



The built in 40° degree pitch

Allows to handle any extreme roof pitch (35° - 65°), sleeve flexibility accommodates vibration and pipe movement caused by expansion/contraction.

Easy on-site customization accommodates all normal installations.



Pipe Size	Compound	Part No.		Flashing Details	
Extreme Angle 1/4" - 5-3/4" (6 - 146mm)	Black EPDM	EA101BA		A-Top opening diameter	Closed
	Silicone	EA102RA	B-Cut to suit pipe size	1/4" - 5-3/4" (6 - 146mm)	
			C-Base dimensions	11" (279mm)	

To see our complete product line go to www.aztecwasher.com

