




INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Square Round Washer Head Type 17 Coarse Wood Screws Lubricized Finish

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point
8 x 1-1/4	10	6,000	DLRWSQL081104	#2	Round Washer	Single Lead	Type 17
8 x 1-1/2	10	5,000	DLRWSQL08112	#2	Round Washer	Single Lead	Type 17
8 x 2	10	3,000	DLRWSQL08200	#2	Round Washer	Single Lead	Type 17
8 x 2-1/2	10	2,000	DLRWSQL08212	#2	Round Washer	Single Lead	Type 17
8 x 3	10	1,500	DLRWSQL08300	#2	Round Washer	Single Lead	Type 17

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Lubricized is a dry touch lubricant which aids in the reduction of torque needed to drill fasteners
<i>application:</i>	wood to wood applications.
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meets or exceeds the following specifications:

ASME B 18.6.1	Standard Specification for Wood Screws
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus

Ultimate Value Chart

DIAMETER	2 x 4 Red Wood Pull Out	3/4 Particle Board Pull Out	2 x 4 Fir Pull Out	Minimum Torsional Strength (Lb)
#8	518	290	540	39

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DLRWSQL