DRAWING NUMBER S2143

SIZE

SCALE:

NONE

5-17-85

DATE:

APPROVED BY: **TD**

СНЕСКЕD ВҮ: **ТD**

DRAWN BY: **PJ**




LOCATION

WITH HEAVY DUTY TRACTOR GRATE

15" (380) ROUND TOP - HEAVY DUTY DRAINS

Load Rating: Heavy Duty having a Safe Live (Static) Load between 5,000 lbs. (2,250 kg) and 7,499 lbs (3,375 kg) per ASME A112.6.3 Floor Drain Standard. For the specific Safe Live Load rating of any grate, contact the Smith representative or factory direct.

> Free Area 45 SQ IN (290) SQ CM



A (Pipe Size) = 02(50), 03(75), 04(100), 05(125), 06(150) or 08(200)

Fig. 2143C.....CAULK OUTLET Fig. 2143T.....THREADED OUTLET

 \triangle Add 1/4" (6) when bronze top is specified.

REGULARLY FURNISHED:

Duco Cast Iron Body and Flashing Collar with Cast Iron ADA Tractor Grate.

VARIATIONS:

Dome Grate -D Flat Bottom Strainer -FBS

NO-HUB Adaptor (Specify Fig. 2646Y)

Square Top -S

Vandal Proof -U 4"(100) High Collar -HC4

Quad Close Trap Seal (Specify Fig. 2692)

Bucket -B

OPTIONAL MATERIALS:

Ductile Iron Grate -M Galvanized Cast Iron -G Nickel Bronze Top -NB

Polished Bronze Top -PB Stainless Steel (Specify Fig. 9733)

NOTE: Dimensions shown in parentheses are in millimeters.

K J H G	7-22-19 6-17-19 6-12-15 4-14-14	Added Load Rating Removed Function Revised Variations Added Free Area	MW MW TBW TBW	JM JM CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 2143
REV.	DATE	DESCRIPTION	BY	CKD. BY			