

Fastener Data Sheet

Sizes & Quantities:

#	Shank Length	Shank Gauge	Fastening Range Max. Total Thickness	Required Deck Penetration	*Pieces / Pound	25 Lbs. Box	
						*Pieces /Box	Pounds /Box
1	3/4"	9	-	3/4"	84	2,100	25
2	7/8"	9	-	7/8"	75	1,875	25
3	1"	9	-	1"	76	1,900	25
4	1 1/4"	9	1/4"	1"	70	1,750	25
5	1 1/2"	9	1/2"	1"	64	1,600	25
6	1 3/4"	9	3/4"	1"	59	1,475	25
7	2"	9	1"	1"	52	1,300	25
8	2 1/2"	9	1 1/2"	1"	40	1,000	25
9	3"	9	2"	1"	28	700	25
10	3 1/2"	9	2 1/2"	1"	16	400	25
11	4"	9	3"	1"	4	100	25

*Approximate Count



Design Options:

Uses:

Design Features:

- Wider gauge shank to increase strength and hold
- Head and nail shank are welded together (an exclusive feature)
- The "original" capped roofing nail
- Installed with hand hammer
- Round head will not puncture roof membrane
- Fits perfectly in the 2" and 3" Simplex Rupture Discs
- Fast, Affordable, and Strong

- Base sheet fastener (deck or wall)
- Roof membrane fastener (deck or wall)
- Base flashing fastener (wall)

Approvals:

American Plywood Association
FFN-105b Type II, Style 27

Notes:

Ideal for curtain walls and parapets.

Rupture Discs:

Made of Galvalume metal to prevent corrosion
Designed to fit all simplex nails
Disc will increase rupture resistance to softer metals
2" Rupture Disc is recommended for base sheet attachment
3" Rupture Disc is recommended for insulation attachment.

Disc Diameter	Disc Shape	Disc Design	*Pieces /Pound	*Pieces /Box	Pounds /Box
2"	Round	Parabolic	50	1000	20
3"	Round	Parabolic	23	1000	45