



**DESIGN FEATURES**

- Chloramine resistant washers
- Exclusive POWR-TIGHT 12 point crimp - many times industry standard
- Withstands dramatic changes in water pressure
- Easy installation, no special tools or soldering required

**OPERATING SPECIFICATIONS**

- Working Temperature: 40°F-160°F with intermittent temps up to 180°F
- Working Pressure: 20-125 PSI with intermittent impulse up to 180 PSI

**MATERIAL SPECIFICATIONS**

- Tubing: LSP's Patented UltraCore™
- End Fittings: Brass
- Connection Nuts: Nickel Plated Brass
- Washers- NSF/ANSI 61 Compliant

**ULTRACORE™  
LARGE DIAMETER CONNECTORS  
Specification Sheet**

Part Number	Description	Length
PPC-118-PP	1/2" FIP x 1/2" FIP x 1/2" ID	18"
PPC-124-PP		24"
HWH-118-PP	3/4" FIP x 3/4" FIP x 1" ID	18"
HWH-124-PP		24"
HWH-148-PP		48"
SFF-10012	1" FIP x 1" FIP x 1" ID	12"
SFF-10018		18"
SFF-10024		24"
SFF-10036		36"
TMX-10020	1" ID - 1" MIP x 1/2" Ground Joint FIP with 1/2" MIP Adaptor*	20"
TMX-10036		36"
TMX-10048		48"
TMX-10072		72"
TMX-10096		96"
TMX-07512	3/4" ID - 3/4" MIP x 3/4" Ground Joint FIP with 3/4" MIP Adaptor*	12"
TMX-07524		24"
TMX-07536		36"
TMX-07548		48"
TMX-05018	1/2" ID - 1/2" MIP x 1/2" Ground Joint FIP with 1/2" MIP Adaptor*	18"
TMX-05024		24"
TMX-05036		36"

**COMPLIANCES/LISTINGS**

- ASME A112.18.6/CSA B125.6 Through IAPMO, File #2111
- NSF/ANSI 61 Through IAPMO, File # N-6614
- \*TMX Series Hoses are NOT Lead Free Compliant



**NSF/ANSI 61**

Lead Free Compliant



3689 Arrowhead Drive, Carson City, NV 89706  
 Phone (800) 854-3215 Fax (800) 243-1777  
 E-mail sales@lspproducts.com  
 Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. Rev. 6/17

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	