

## Exterior Nails


### Roofing Nail — Smooth Shank

#### Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate

#### Installation Tips:

- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



#### Copper

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
—	¾	11	0.120	¾	0.375	302	C7511RN1	C7511RN5	C7511RNB
2d	1	10	0.131	7/16	0.438	187	—	C210RN5	C210RNB
2d	1	11	0.120	¾	0.375	229	C211RN1	C211RN5	C211RNB
3d	1¼	10	0.131	7/16	0.438	147	C310RN1	C310RN5	C310RNB
3d	1¼	11	0.120	¾	0.375	187	C311RN1	C311RN5	C311RNB
4d	1½	10	0.131	7/16	0.438	123	C410RN1	C410RN5	C410RNB
4d	1½	11	0.120	¾	0.375	155	C411RN1	C411RN5	C411RNB
5d	1¾	10	0.131	7/16	0.438	112	C510RN1	C510RN5	C510RNB
5d	1¾	11	0.120	¾	0.375	139	C511RN1	C511RN5	C511RNB
6d	2	10	0.131	7/16	0.438	93	C610RN1	C610RN5	C610RNB
6d	2	11	0.120	¾	0.375	124	C611RN1	C611RN5	C611RNB
8d	2½	10	0.131	7/16	0.438	81	C810RN1	C810RN5	C810RNB
8d	2½	11	0.120	¾	0.375	108	—	—	C811RNB
10d	3	10	0.131	7/16	0.438	67	C1010RN1	C1010RN5	C1010RNB