



Technical Data

**Stainless Steel
Roofing Nails**
Smooth or Ring Shank



Length	Gauge	Shank Diameter	Head Diameter	Count/Lb.
3/4"	12	.109	5/16"	380
1"	12	.109	5/16"	348
1 1/4"	12	.109	5/16"	255
1 1/2"	12	.109	5/16"	218
1 3/4"	12	.109	5/16"	189
2"	12	.109	5/16"	170
3/4"	11	.120	11/32"	323
1"	11	.120	11/32"	244
1 1/4"	11	.120	11/32"	199
1 1/2"	11	.120	11/32"	170
1 3/4"	11	.120	11/32"	149
2"	11	.120	11/32"	136
3/4"	10	.134	3/8"	212
1"	10	.134	3/8"	166
1 1/4"	10	.134	3/8"	139
1 1/2"	10	.134	3/8"	126
1 3/4"	10	.134	3/8"	105
2"	10	.134	3/8"	91
3"	10	.134	3/8"	78

FEATURES

- Large Flat Head·Diamond Point·
- Lasting corrosion protection for all roofing materials·
- Smooth shank or annular styles in stock·
- Recommended first choice for fiber cement roofing & siding products·
- 304 Stainless Steel·**

511 Central Park Drive, Sanford, Florida 32771-6653
407.328.5300 800.334.9815 407.328.5250 (fax)