

Location: \_\_\_\_\_



**R1220-G**

**MEDIUM SUMP I.R.M.A ROOF DRAIN WITH STAINLESS STEEL BALLAST GUARD**

**Specification:** MIFAB® Series R1220-G lacquered cast iron medium sump roof drain with 12" diameter anchor flange, large cast iron waterproofing membrane clamp ring with integral gravel stop, 5" high stainless steel ballast guard and standard self-locking cast iron dome strainer with a free area of 71.50 square inches.

**Function:** Used in any type of flat roofs where a medium sized drain is required. Wide anchor flange and membrane clamp with deep groove design provides for secure grip of membrane and roof flashing materials. Ballast guard prevents ballast from entering drain line.

**71.50 In<sup>2</sup> FREE AREA DOME**

**PARTS:**

*Metric equivalents see chart below. (Dimension) Denotes Millimetres* R1220-G Series meets ASME roof drain standard A112.6.4-2003

| PIPE SIZE | BODY HEIGHT       |                  |
|-----------|-------------------|------------------|
|           | NO HUB (STANDARD) | INSIDE CAULK (X) |
| 2" (51)   | 6 1/2" (165)      | 6.575 (167)      |
| 3" (76)   | 6 1/2" (165)      | 6.575 (167)      |
| 4" (102)  | 6 1/2" (165)      | 6.575 (167)      |
| 6" (152)  | 6 1/2" (165)      | 6.575 (167)      |

|               |   |               |  |
|---------------|---|---------------|--|
| <b>SUFFIX</b> | <b>OPTIONAL VARIATIONS</b>                  | <b>SUFFIX</b> | <b>OPTIONAL VARIATIONS</b>                                   |
| -6            | Vandal proof dome (metal dome only)         | -JC           | S.S. ballast guard with secondary clamp                      |
| -11           | Acid resistant epoxy coating                | -PA           | Pennsylvania Steel Act compliant product                     |
| -12           | Galvanized metal dome                       | -R            | 2" external water dam  |
| -12A          | Galvanized body and membrane clamp          | -RG           | RoofGuard non clogging cast iron dome                        |
| -13           | Galvanized body, membrane clamp and dome    | -U            | Underdeck clamp  |
| -83           | Stainless steel mesh screen over metal dome | -U3           | Underdeck clamp with cutaway side                            |
| -B            | Sump receiver                               | -W-1          | Water proofing flange  |
| -BA           | Buy America Act compliant product           | X             | Inside caulk outlet (2",3",4")                               |
| -E            | Adjustable extension                        | -XJ           | Vertical expansion joint (see R1900)                         |
| -EG           | Galvanized Adjustable extension             | -Z            | Extended wide elastomeric flange (20" diameter x 1/4" thick) |
| -HC           | Adjustable ballast guard with sec. clamp    |               |  |

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: \_\_\_\_\_ Page No: \_\_\_\_\_  
 Section No: \_\_\_\_\_ Contractor: \_\_\_\_\_  
 Schedule No: \_\_\_\_\_ Purchase Order No: \_\_\_\_\_