

Residential Master Flash®

“Environmentally safe” lead free aluminum base.

Advanced Ozone Resistance tested to...	EPDM 70 hour @ 500 pphm	HIGH TEMP RED/GRAY SILICONE 70 hour @ 500 pphm
High Temperature Resistance Tested to	Intermittent Continuous	
	+135°C (+275°F) +100°C (+212°F)	+260°C (+500°F) +225°C (+437°F)
Low Temperature Resistance tested to...	-55°C (-67°F)	-74°C (-101°F)
Compression Set Maximum...	25%	50%

*Complete specification data and testing methods are available upon request.

For the Residential Roofing Industry

Available in four sizes

A “C20” ASTM additional requirement was added to assure conformance to the most stringent ozone/weathering specifications available. This addition allows the rubber a 20 year life.

The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature which enables it to be used with type “B” vents. Listed with IAPMO certification No.3121



The pull tab design and easy smooth tear grooving is intended to eliminate razor knives and allow for a circular hole

Unique compression seal technology

Weather Protection Made of EPDM or High Temp Red/Gray Silicone,


These flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.

The built in 20° pitch allows adaptability to almost any roof pitch including 45°

Easy on-site customization accommodates all normal installations.


Sleeve flexibility absorbs vibration and pipe movement caused by expansion/contraction

“Environmentally safe” lead free aluminum base.




Mini Residential Flashing Details

A-Top Opening	Closed
B-Pull to suit pipe size	1/4”-3” (6-76mm)
C-Base	16”x19-1/4” (410x490mm)




#1 Residential Flashing Details

A-Top Opening	2-1/2” (63mm)
B-Pull to suit pipe size	3”-8” (76-203mm)
C-Base	20”x24” (508x609mm)



#2 Residential Flashing Details

A-Top Opening	5-5/8” (142mm)
B-Pull to suit pipe size	8”-11” (203-279mm)
C-Base	26”x30” (660x762mm)



#3 Residential Flashing Details

A-Top Opening	8-3/4” (222mm)
B-Pull to suit pipe size	11”-18” (279-457mm)
C-Base	35”x 35” (889x889mm)