

A172.8FGVR Series

MODEL A172408S-FG-VR

Barrier Free, 14 Gage Stainless Steel,
Enhanced Vandal Resistance,
Bi-level, Wall Mounted Water Cooler

STANDARD FEATURES

- Child or Adult ADA Compliant (when properly installed)
- 14 gage stainless steel apron, basin and front access panel
- Lead-Free Stainless Steel, anti-rotation, non-squirt bubblers
- 100 mesh inlet strainer
- Vandal resistant screws
- Hanging bracket provided
- Auto-stop allows service of cartridge and strainer without shutting off water supply

SUGGESTED SPECIFICATIONS

Model A172408S-FG-VR is a self-contained, enhanced vandal resistant bi-level pressure water cooler that shall deliver a minimum of **8.0 GPH** (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90° (32.2°C) ambient. Units shall be activated by chrome plated brass front pushbuttons by using less than 5 pounds of force. Bubblers shall be Lead-Free Stainless Steel with an integrally designed non-squirt feature and operate on a water pressure range of 20-105 psig. **Unit shall be constructed from 14 gage, 304 stainless steel** with an integral drain and the louvers shall have a stainless steel protective screen. Cooling system shall use R-134a refrigerant and be capillary tube controlled. An adjustable thermostat with an off position shall control the refrigeration system. Unit is certified to ANSI A117.1 and NSF/ANSI, Section 9 requirements and Public Law 111-380. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately. Unit shall be listed by Underwriters Laboratories for both the US and Canada, compliant to the Air Conditioning and Refrigeration Institute Standard 1010.

Model Number	GPH*	Rated Watts	Full Load Amps	Approx. Shipping Weight
A172408S-FG-VR	8.0	400	4.4	140 lbs.

* GPH of 50°F water at 90°F ambient room temperature and 80°F inlet water temperature
Compressor motor operates on 115 Volt / 60 Hz single phase.



Complies with the following standards: CHSC 116875
Test rating conditions are compliant with ARI 1010.



Model A172408S-FG-VR Shown
PATENT# 10,100,933



“RATED FOR INDOOR USE”

MODEL:

(Must Specify)

- A172408S-FG-VR Satin Stainless Finish

OPTIONS

(additional costs may be incurred)

- CSC3 Concealed support carrier
- RBL Reverse bi-level
- SK9 Skirt kit, stainless steel, for upper unit
- WB2 Wall bezel, stainless steel
- WF1 1500 gallon capacity, NSF 42+53, 1 micron lead reduction filter
- 220V 220 volt / 50 Hz compressor


⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



WATER COOLERS

A172.8FGVR Series MODEL A172408S-FG-VR

BARRIER FREE, 14 GAGE STAINLESS STEEL,
ENHANCED VANDAL RESISTANCE,
BI-LEVEL WALL MOUNTED WATER COOLER



GENERAL NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MM]
 2. ALLOW 4 INCHES [102 MM] MINIMUM CLEARANCE PER SIDE FOR VENTILATION
 - *3. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES
 4. STOP VALVE, P-TRAP, & ELECTRICAL OUTLET NOT SUPPLIED
 5. IMPORTANT: COOLERS MUST BE ATTACHED TO WALL WITH APPROPRIATE WALL ANCHOR SCREWS
- A. 3/8" NCT SUPPLY INLET
 - B. WASTE OUTLET FOR 1-1/4" P-TRAP BY OTHERS
 - C. ELECTRICAL SERVICE ROUGH
 - D. Ø3/8" HANGER BRACKET PUNCHING, 3 PLACES FOR ANCHORING HARDWARE BY OTHERS
 - E. Ø1/4" PUNCHING, 2 PLACES FOR ANCHORING HARDWARE BY OTHERS

Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING	Model Number & Options _____	Quantity _____	All dimensions are subject to manufactures tolerance of plus or minus 1/2" nominal and subject to change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.
	Company _____		
	Contact _____	Title _____	
	Signature (Approval for Manufacturing) _____	Date _____	

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA
Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of
MORRIS GROUP
INTERNATIONAL