

Termination and Batten Bars

.050", .075", .090", .100", .125", 6" OC

For wall termination applications

- Manufactured from specially extruded aluminum without sharp edges.
- Reinforced strengthening ribs allow for use in high wind applications.


- K-Fast fastener and batten bar combination reduces labor due to enhanced fastening pattern approvals.

Application

Ribbed Term Bar w/ Lip

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike™





Dimensions: .050" (edge) x .075" (ribs) x 1" wide x 10' long
 Holes: .260" x .380" slotted at 6" O.C. spacing
 Material: Extruded Aluminum

Ribbed Term Bar

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike




Dimensions: .075 (edge) x .100" (ribs) x 1" wide x 10' long
 Holes: .260" x .380" slotted at 6" O.C. spacing
 Material: Extruded Aluminum

Lip & Ball Term Bar

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike





Dimensions: .088" x 1" wide x 10' long
 Holes: .280" x .380" slotted at 6" O.C. spacing
 Material: Extruded Aluminum

Gravel Stop/Drain Bar

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike



Dimensions: .110" x 3.50" wide x 10' long
 Holes: .300" x 1.62" slotted at 4" O.C. spacing
 Material: Extruded Aluminum

Notes

Dimensions are nominal inches unless noted. Ultimate values listed are the result of laboratory testing. Pull out (pounds ultimate) strength values may vary from tabulated loads depending upon the uniqueness of the application. The specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners.

Continued on following page

Termination and Batten Bars

.050," .075," .090," .100," .125," 6" OC

For wall termination applications

Selection

Termination Product	Part No.	Carton Wt. (lbs)	Hole Spacing	Carton Qty.	Skid Qty.
Flat Batten Bar (.050)	0625833	45	6"	500 feet (50-10 ft pcs)	10,000
.050" All Purpose	H3000	45	6"	500 feet (50-10 ft pcs)	10,000
.075" Single Lip	H3030	51	6"	500 feet (50-10 ft pcs)	10,000
.075" Ribbed Single Lip	H3035	51	6"	500 feet (50-10 ft pcs)	10,000
.100" Single Lip	H3090	68	6"	500 feet (50-10 ft pcs)	10,000
.125" Flat	H3120	78	6"	500 feet (50-10 ft pcs)	10,000
.100" Ribbed Term Bar Flat	H3125	78	6"	500 feet (50-10 ft pcs)	10,000
Drain Bar/Gravel Stop	H3150	42	6"	100 feet (10-10 ft pcs)	10,000
.090" Lip and Ball	H3155	86	6"	500 feet (50-10 ft pcs)	10,000
Coiled Batten Bar (Twin-Lok)	H3700	72	3"	500 feet (50-10 ft pcs)	10,000
Coiled Batten Bar (.260)	H3900	72	3"	500 feet (50-10 ft pcs)	10,000

Approvals

Dekfast fasteners and plates are Factory Mutual approved for attachment of insulation board and/or roof cover to roof deck. Refer to FM Approval Guide and Supplements for current FM approved insulation fastening patterns. Termination products exceed Factory Mutual corrosion-resistance Standard 4470.

Options

Coatings



ZAC® Anchors & Nailins

