

Location: _____



MI-O-BO

BOLT ON (FIXED) EXPRESSIONS FOR MI-O SERIES OF OIL INTERCEPTORS

Specification: MIFAB MI-O-BO Series (specify Model #) of fixed bolt on extensions are manufactured from 10 gauge powder epoxy coated steel and are complete with lid sealing neoprene gasket and lockdown hardware.

Function: Ideal for installations where the height of the interceptor needs to be increased to meet the finished floor while leaving the inlet and outlet locations the same. The original lid of the interceptor is removed and the bolt on extension is placed on top of the lid sealing gasket. The original interceptor lid is then placed on top of the bolt on extension (lid sealing gasket is provided for the top of the bolt on extension). The extra long lockdown hardware provided with the bolt on extension is used to secure the lid to the cross bar supports.



MODEL NO.	USE WITH	US GPM	"A" LENGTH	"B" WIDTH	"E" HEIGHT	NO. OF BOLTS
MI-O-BO-A-6	MI-O-A	10	21.25"	15.75"	6"	1
MI-O-BO-B-6	MI-O-B	15	23.25"	15.75"	6"	1
MI-O-BO-C-6	MI-O-C	20	21.25"	15.75"	6"	1
MI-O-BO-1-6	MI-O-1	25	28"	22"	6"	4
MI-O-BO-2-6	MI-O-2	35	34"	24"	6"	4
MI-O-BO-3-6	MI-O-3	50	34"	24"	6"	4
MI-O-BO-4-6	MI-O-4	75	48"	34"	6"	8
MI-O-BO-5-6	MI-O-5	100	51"	36"	6"	8
MI-O-BO-6-6	MI-O-6	125	53"	36"	6"	8
MI-O-BO-7-6	MI-O-7	150	58"	36"	6"	12
MI-O-BO-8-6	MI-O-8	200	68"	38"	6"	24
MI-O-BO-9-6	MI-O-9	250	74"	40"	6"	24
MI-O-BO-10-6	MI-O-10	300	78"	44"	6"	24
MI-O-BO-11-6	MI-O-11	350	80"	46"	6"	24
MI-O-BO-12-6	MI-O-12	400	82"	48"	6"	24
MI-O-BO-13-6	MI-O-13	450	84"	50"	6"	24
MI-O-BO-14-6	MI-O-14	500	86"	52"	6"	24

Job Name: _____ Page No: _____
 Section No: _____ Contractor: _____
 Schedule No: _____ Purchase Order No: _____

MIFAB reserves the right to make changes in material and design without formal notice and obligation.