



Maze Nails

Product Specification Sheet

Hot-Dip Galvanized Ring Shank Asphalt & Fiberglass Shingle Nails

Stock Number: R100A

MATERIAL	Medium Carbon Steel
LENGTH	7/8"
SHANK DIAMETER	0.121"
HEAD DIAMETER	.375"
SHANK STYLE	Ring Thread
POINT STYLE	40 degree diamond
COATING	Double Hot-Dip Galvanized
APPROX. NAILS PER LB	272.0

Product Description

Designed for the secure application of asphalt and fiberglass shingles on new construction and re-roofing jobs. Ring shank provides extra holding power, especially in high wind/hurricane areas. STORMGUARD® Double Hot-Dipped Zinc-Coating provides extra corrosion-resistance in sea coastal areas. Type 304 Stainless Steel Roofing Nails also available. Manufactured to meet federal spec. FFN-105-B and ASTM spec. A-153 for hot-dip zinc coating. Nails should be long enough to penetrate 3/4" into the wood deck lumber, or completely through plywood decking. All Maze Nails are 100% Made in the U.S.A. SIZES AND QUANTITIES COMMONLY USED On A New Roof - 1-1/4" - 320 nails per sq. or 1-3/4 lbs. Over An Old Roof - 1-3/4" - 320 nails per sq. or 2-1/4 lbs.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet



Maze Nails

Product Specification Sheet

100% MADE IN THE USA