



# FLEX ARRESTER™

## Specification Sheet



Part Number	Description	Use	Length	Listing*
DWFA-160-PP	3/8" COMP SC X 3/8" COMP SC w/ 1/2" NPT 90 degree elbow. Arrester 12" from valve	Dishwasher	60"	1, 2, 4
DWFA-560-PP	3/8" COMP x 3/8" COMP w/ 3/4" FGHT 90 degree elbow. Arrester 12" from valve	Dishwasher	60"	1,2,4
IMFA-160-PP	1/4" COMP HC X 1/4" COMP HC	Icemaker	60"	1, 2, 3, 4
WMFA-160-PP	3/8" ID, 3/4" FGHT x 3/4" FGHT	Washing Machine	60"	1, 4
FCFA-120-PP	3/8" Comp x 1/2" FIP	Faucet	20"	1, 2, 3, 4
WCFA-112-PP	3/8" Comp x 7/8" Ballcock	Toilet	12"	1, 4

### DESIGN FEATURES

- Easy to Install
- Size AA, ASSE 1010 certified.
- No access panel or maintenance required
- May be installed at any angle
- Patented Inline Hammer Arrester eliminates water hammer
- Exceeds all ASTM A112.18.6 Flow requirements
- 5 year warranty
- 100% Lead Free Compliant
- Is effective when installed in any direction

### MATERIAL SPECIFICATIONS

- Corrosion resistant polymer braid
- Taste and odor free patented Ultracore™ liner
- Chloramine resistant soft cones
- End Fittings and Nuts, Brass
- SS Ferrule

### OPERATING SPECIFICATIONS

- Temperature: 40-160°F
- Max working pressure 125 PSI

### CAUTION

- Keep away from Solvents/Cements/Primers
- Keep out of constant direct sunlight
- For Indoor Use Only

ACCESSORIES/REPLACEMENT PARTS	
P-06365	Male 3/8" Comp x 3/4" FGHT Elbow Adaptor

### MAINTENANCE

- Keep hose assembly dry
- Inspect every six months and replace immediately in the event of leaks, wear, discoloration and any visible signs of corrosion
- Do not re-use



P-06365

### COMPLIANCES/LISTINGS (\*See Table for specific applications)

1. IAPMO listed to ASME A112.18.6. File 2111
2. IAPMO listed to Lead Free Plumbing Law, File 6545
3. IAPMO listed to NSF/ANSI 61, File N-6614
4. IAPMO listed to ASSE 1010, File 4541



**NSF/ANSI 61**  
**ASSE 1010**



Lead Free Compliant

### INSTALLATION INSTRUCTIONS:

1. Install with water flow in direction of arrow
2. Position Flex Arrester to prevent damage from appliance when moved
3. Hand-tighten inlet to supply valve. Add ¼ turn with wrench. Do not over tighten
4. If Elbow Adaptor is needed: Use Teflon Tape on the male thread, tighten to appliance
5. Hand-tighten outlet to elbow adaptor. Add ¼ turn with wrench. Do not over tighten
6. Brass nuts hand-tighten outlet to appliance. Add ¼ turn with wrench. Do not over tighten
7. Plastic nuts hand-tighten only. Do not over tighten
8. Do not twist, kink, crush or pull line up against fitting
9. After installation, check for leaks



3689 Arrowhead Drive, Carson City, NV 89706

Phone (800) 854-3215 Fax (800) 243-1777

E-mail sales@lspproducts.com

Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. (Rev 10-17)

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	