

TRADITIONAL DRINKING FOUNTAINS

Special Application

MODEL M-PFS

PET FOUNTAIN

STANDARD FEATURES

Model M-PFS pet fountain features design simplicity. This unit includes a single aluminum alloy fountain bowl. The fountain is operated by a self closing spigot valve. Standard model is seasonal, not freeze resistant. Heavy-duty construction ensures durability and field-servicable components are easily accessible. Base is finished in Chestnut Brown.

SUGGESTED SPECIFICATIONS

Pet fountain shall be Murdock model M-PFS. Unit shall be furnished with one fountain bowl mounted on the pedestal.

Pedestal shall be a heavy duty iron casting and base of pedestal shall have four mounting holes. Pedestal shall be finished with a heavy grade of oil-based brown enamel.

Bowl shall be round, aluminum alloy casting two 3/8" holes for draining.

Spigot valve shall be self-closing, handle operated and constructed of cast brass with a rough chrome plated finish. Supply line shall be lead free brass piping with 1/2" NPT connection.

All solid brass castings shall conform to ASTM standards B61 and B62. Spigot valve conform with lead-free requirements of NSF61, Section 9, 1997 and Federal Public Law 111-380.



☐ Standard Model: M-PFS

OPTIONS

(additional costs may be incurred)

🔲 - CV1 Cartridge Valve with Pushbutton and Spout

(Not available with -FRU1 option)

☐ - FRU1 Underground Freeze Resistant option ¹

(Air Valve Pushbutton replaces Spigot)

🔲 - BLACK Pedestal color black

☐ - GREEN Pedestal color green

Options Notes:

¹ See separate option sheet.

Custom color finishes available upon request.

Please visit www.murdockmfa.com for most current specifications.







Complies with the Conserving Product following standards: ANSI/NSF 61.9








TRADITIONAL DRINKING FOUNTAINS


8/4 [210] 13¹/₂ [343]


Special Application

MODEL M-PFS
PET FOUNTAIN



Optional -CV1 Cartridge Valve with Pushbutton and Spout





Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SUMMARY AL FOR TURING	Model Number & Options	mber & OptionsQuantity	All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.
SELECTION (& APPROV MANUFAC	Contact Signature (Approval for Manufacturing)	_Title	

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GR

06/22/21