DRAWING NUMBER S4438

NONE

SJM **APPROVED**

SJM

CHECKED BY:

DRAWN

IGURE IUMBER

TOLERANCE AND CHANGE WITHOUT

SUBJECT TO MANUFACTURERS

DATA

VOID


, R

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED

CAULK FERRULE CLEANOUTS WITH FRAME AND COVER

LEAD SEAL PLUG WITH FRAME AND SCORIATED COVER

FUNCTION: Used in wall openings where a caulk ferrule/taper thread plug is provided for accessibility to the building waste piping. Face-of-Wall or Flush-with-Wall covers provided to conceal opening in finished wall. Ribbing on outside of ferrule prevents turning of ferrule in the caulking lead.



Anchor Lugs G SQ FSQ В Secured Cover (19)

FIG. 4438C FACE-OF-WALL COVER

FIG. 4439C FLUSH-WITH-WALL COVER

Α	B OPENING		С	D	E	F	G
SIZE	DIA	SQ	SIZE		DIA	SQ	SQ
02 (50)	4 (100)	6 x 6 (150) x (150)	1 1/2 (38)	2 1/2 (64)	4 1/2 (115)	7 (180)	5 1/2 (140)
03 (80)	5 1/2 (140)	6 x 6 (150) x (150)	2 1/2 (64)	2 3/4 (70)	5 3/4 (145)	7 (180)	5 1/2 (140)
04 (100)	6 (150)	6 x 6 (150) x (150)	3 1/2 (89)	3 (76)	6 1/2 (165)	7 (180)	5 1/2 (140)
05 (125)	6 (150)	8 x 8 (205) x (205)	4 1/2 (115)	3 (76)	6 1/2 (165)	9 (230)	7 1/2 (190)
06 (150)	8 (205)	8 x 8 (205) x (205)	5 1/2 (140)	3 (76)	8 1/2 (215)	9 (230)	7 1/2 (190)

NOTE: Dimensions shown in parentheses are in millimeters.

REGULARLY FURNISHED:

Duco Cast Iron Caulk Ferrule with Cast Iron Lead Seal Plug and Secured Scoriated Nickel Bronze Cover and Frame with Anchor Lugs. Type of Cover as Indicated by Figure Number Selected.

VARIATIONS:

TBW TBW

TRW

EMB

Cover Drilled in Center and Furnished with 1/4"(6)-20 x 2 1/2"(64) Long Screw "T" Handle Plug -TH

Plug Tapped 1/4"(6) -20 Thread Vandal Proof Screws-U

OPTIONAL MATERIALS:

Cast Bronze Body -BB Cast Bronze Plug -BP

Polished Bronze Frame and Cover -PB

HGE	10-7-14 10-3-13 7-15-13 8-11-97
Ę	7-15-13
Ε	8-11-97

DATE

REV.

Revised Variations Revised Function Rev. Table
Chg'd Opt Mat

vised Variations vised Function v. Table g'd Opt Mat	
DESCRIPTION	Γ

BW SJM CL BS	1
CKD. BY	

4438, 4439