DRAWING NUMBER S4510

NONE

2-16-70

APPROVED

CHECKED BY:

DRAWN BY:

SERIES

4530

4510,

FIGURE NUMBER

RP

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR





LOCATION

CLEANOUT TEES

WITH COUNTERSUNK PLUG AND ROUND ACCESS COVER

FUNCTION: Used in concealed drainage lines where a cleanout is desired. Removable face-of-wall cover allows easy access to closure plug.





LESS COVER AND SCREW

WITH COVER AND SCREW

Fig. 4510S GASKET SEAL - IRON PLUG	Fig. 4530S
Fig. 4511S GASKET SEAL - BRONZE PLUG	Fig. 4531S
Fig. 4512S TAPER THREAD - BRONZE PLUG	Fig. 4532S

Α	В	С	D	Е	F
SIZE	DIA		SIZE		
02 (50)	4 1/4 (110)	10 1/2 (265)	1 1/2 (38)	6 1/4 (160)	2 (51)
03 (75)	5 1/2 (140)	11 3/4 (300)	2 1/2 (64)	7 (180)	2 1/2 (64)
04 (100)	5 1/2 (140)	12 (305)	3 1/2 (89)	7 (180)	3 (76)
05 (125)	7 (180)	*13 (330)	4 1/2 (115)	8 1/2 (215)	4 (100)
06 (150)	9 1/4 (235)	16 (405)	6 (150)	9 (230)	4 1/2 (115)

* This Dimension becomes 15 (380) for the 4512 and 4532.

Spigot Outlet Sized for Service Weight and/or NO-HUB for 02(50) - 05(125) Sizes

REGULARLY FURNISHED:

Duco Cast Iron Cleanout Tee and Countersunk Plug with Stainless Steel Round Cover and Screw as Indicated by Figure Number Selected.

VARIATIONS:

Longer Center Screw (Specify Length)

"T" Handle Plug -TH

(Plug Tapped 1/4" (6) -20 Thread)
Vandal Proof Screw -U (Fig. 4530 Series)

Y NO-HUB Both Ends 2(50), 3(75) & 4"(100) sizes only

OPTIONAL MATERIALS:

Polished Bronze Cover -PB
Prime Coated Steel Cover -PC

NOTE: Dimensions shown in parentheses are in millimeters.

H G E		Rev. Table, Outlet Size, Var. Revised Variations Revised Variations Added Metric	TBW TBW JJ EMB	BW BW CL BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 4510 SERIES
REV.	DATE	DESCRIPTION	BY	CKD. BY			4530 SERIES