




INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Phillips Modified Truss Wafer Self Drill Screws Zinc Finish

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Drill Point	Max Drill	Drill Speed
8 x 1/2	18	10,000	MTSDZ08012	#2	#2 PT	0.112"	2500 RPM
8 x 3/4	18	8,000	MTSDZ08034	#2	#2 PT	0.112"	2500 RPM
8 x 1	18	5,000	MTSDZ08100	#2	#2 PT	0.112"	2500 RPM
8 x 1-1/4	18	5,000	MTSDZ081104	#2	#2 PT	0.112"	2500 RPM
8 x 1-5/8	18	4,000	MTSDZ08158	#2	#2 PT	0.112"	2500 RPM
8 x 1-7/8	18	3,000	MTSDZ08178	#2	#2 PT	0.112"	2500 RPM
8 x 2	18	3,000	MTSDZ08200	#2	#2 PT	0.112"	2500 RPM
8 x 2-1/2	18	2,500	MTSDZ08212	#2	#2 PT	0.112"	2500 RPM
8 x 3	18	2,000	MTSDZ08300	#2	#2 PT	0.112"	2500 RPM

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Zinc Finish provides 24 hour minimum salt spray corrosion resistance
<i>application:</i>	metal to metal applications.
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side of the metal.

Meets or exceeds the following specifications:

AC118	Acceptance criteria for tapping screw fasteners used in steel-to-steel connections
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1513 (18)	Standard Specification for Steel Tapping Screws for Cold-Formed Steel Framing Connections
ASTM C954 (18)	Standard Specification for Steel Drill Screws for the Application of Gypsum Panel Products or Metal Plaster Bases to Steel Studs from .033 to 0.112 in. in Thickness
SAE J78	Standard for Dimensional, Mechanical and Performance Requirements

Ultimate Value Chart

	DIAMETER	Nom Screw Dia	25 Gauge	22 Gauge	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	Min Torsional Strength (Lb)
Tension (Pull) Lbs 1 pc	8-18	0.164	97	196	285	444	550	924	1100	42 lbs
Shear (Metal to Metal)	8-18	0.164	-	580	829	994	1096	1332	1337	42 lbs

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

MTSDZ08